



# ELECTRONIC HOOK SWITCH (EHS) SOLUTIONS FOR SIEMENS

## SUPPORTED SIEMENS IP PHONES



OpenStage 30/40/60/80



Plus OptiPoint 600



OptiPoint 500 Basic/Std/Adv/Eco



OptiPoint 410/420 Std/Adv



Jabra LINK™ 14201-10 EHS Adapter<sup>1</sup>



Jabra PRO™ 9400 Series

OR



Jabra GO™ 6470

OR



Jabra PRO™ 920

OR



Jabra GN9350e/  
Jabra GN9330e

OR



Jabra GN9120 EHS/  
Jabra GN9125


<sup>1</sup> Also requires Acoustic Adapter from Siemens, must be version 10 or above, SS0817-K7110-8508-10. This does not apply to the OpenStage 40/60/80 phones

## SET UP INFORMATION

To connect your Siemens phone and Jabra headset with the Jabra EHS Adapter cable, just follow these simple steps:

### SETTING UP THE SIEMENS IP PHONE

1. Plug the single end of the Y cable in the headset socket on the phone's headset port.
2. Connect the RJ9 plug in the normal phone socket on the headset base.
3. Connect the large clear plug RJ45 into the phones AUX port.



Compatibility selector  
Jabra GN9350e

### SETTING UP JABRA GN9350e

1. Open up the cover on the base unit.
2. On the LCD display, navigate to the handset picture.
3. Navigate to the DHSG mode and select it by pressing the OK button.
4. Set Compatibility selector in position "A".

### SETTING UP JABRA GN9120 EHS/ JABRA GN9125

1. Set compatibility selector (Telephone Termination Switch Wheel) in position "A".
2. Set the base unit to the DHSG mode by keeping the headset in the base and hold the volume + / - buttons on the headset for 6 seconds until the red light on the base flashes rapidly.
3. Scroll through the four different settings using + / - and set to the lips icon. Leave for 15 seconds until the unit has displayed the confirmation flash sequence and it is ready to go!


### Setting up Jabra PRO™ 9400 and Jabra GO™ 6470 - follow the guide on page 31.

### SETTING UP JABRA PRO™ 920

1. Connect the Jabra LINK™ adapter as shown in adapter documentation supplied with the Jabra LINK™. On some phones the telephone cable will also need to be connected.
2. Call your connected desk phone using another phone to enable the Jabra LINK™ adapter. Wait 10 seconds before answering.
3. Set a clear dial tone. Locate the clear dial tone switch on the back of the Jabra PRO 920 base and rotate to "A".
4. Set the Microphone volume. Make a call to test your speaking volume. The listener should not adjust their own volume. You may adjust your microphone speaking volume using the + / - volume buttons.

### SETTING UP JABRA GN9330e

1. Place the headset in the base with its indicators facing you.
2. Press the Telephone button on the Base for 6 seconds while the headset is in the base until the headset's blue LED is flashing rapidly.
3. Use the volume up/down button to shift between the different EHS settings - see table below.



The base unit's 4 battery indicators show which EHS mode the Jabra GN9330e is in.

GN RHL (Default)	■	□	□	□
DHSG	■	■	□	□
AEI	■	■	■	□
MSH	■	■	■	■



Note: If more than 15 seconds elapse without pressing the volume + or volume - button, the last selected interface will be activated.

